

NOTE:

- 1. GRADE TRANSITIONS SHALL BE CONSTRUCTED AS SMOOTH VERTICAL CURVES.
- 2. THE MAXIMUM DRIVEWAY GRADE SHALL BE 15% UNLESS THE ORIGINAL GRADE AT THE PROPOSED DRIVEWAY LOCATION IS STEEPER. AT NO TIME SHALL THE DRIVEWAY GRADE EXCEED 20%.
- 2. THE MAXIMUM CHANGE IN DRIVEWAY GRADE WITHIN THE RIGHT-OF-WAY SHALL BE 8% ON A CREST CURVE AND 12% ON A SAG CURVE.
- 3. ALL PRIVATE DRIVEWAYS IN THE PUBLIC RIGHT-OF-WAY SHALL BE MAINTAINED BY THE ADJACENT RESPECTIVE PROPERTY OWNER.
- 4. A DRIVEWAY SHALL NOT BE LESS THAN 10 FEET IN WIDTH AND SHALL NOT EXCEED 20 FEET IN WIDTH.
- 5. ONLY GRASS, GRAVEL, AND ASPHALT DRIVEWAY SURFACES ARE ALLOWED IN THE PUBLIC RIGHT-OF-WAY.
- 6. AN ENCROACHMENT AGREEMENT IS REQUIRED FOR ALL EXISTING AND PROPOSED ENCROACHMENTS IN THE PUBLIC RIGHT-OF-WAY. THIS DOCUMENT SHALL BE ENFORCED AS PART OF THE PERMITTING PROCESS.
- 7. SINGLE-FAMILY DRIVEWAYS: 1 DRIVEWAY/ RESIDENCE
- 8. THE FOLLOWING CRITERIA MUST BE MET FOR A CIRCULAR SINGLE-FAMILY DRIVEWAY TO BE APPROVED:
 - A) THE PROPERTY FRONTAGE EXCEEDS 60 FEET: AND
 - B) THE WIDTH OF EACH DRIVEWAY SHALL NOT EXCEED 10'; AND
 - C) SPACING, OFFSETS, AND SETBACKS FROM INTERSECTIONS SHALL BE GOVERNED BY THE MUTCD.

TOWN OF YARROW POINT

4030 95TH AVENUE NE
YARROW POINT. WA 98004
P: (425) 454-6994 F: (425) 454-7899
fownhall@ci.yarrow-point.wa.us
www.ci.yarrow-point.wa.us



DRIVEWAY IN PUBLIC RIGHT-OF-WAY

RD-09

LAST REVISED: 04/06/17